

OUR CAGE FEATURES



TSISCAGE

Every cage partition with **4.0mm diameter wire on top as stiffener** to provide smooth belt return.

SLIDING DOOR

The horizontal sliding door functions easily with a locking system built in the horizontal wire. With the wide opening of the door, it accelerates the placing and removing of birds.

WATERING SYSTEM

2 Nipples drinkers position at centre of cage with a V-Trough underneath are standard. This allows each birds access to 2 nipples. Our watering system features with adjustable **pressure regulator** or **ball tank and end flush** assembly.

CAGE WIRE

Zinc - Aluminium coating of all wire mesh parts before welding and cage floor **reinforced by 3 wires 6.0mm diameter** running longitudinal. Every partition of the cage floor is supported by wire hook floor holder.

CAGE STAND

Levelling Insert :

Heavy duty plastic are used to withstand the challenging environment and for stable cage levelling to optimum feed and water distribution in the system.

FEED TROUGH

Wide and deep design for minimum feed spillage and strong for long life feed trough with **Special Galvanised** coating of 1.0mm thick with anti-waste lip and rounded edges profiles ensure durability, protective and effective.

PP MANURE BELT

Polypropylene (PP) belt 1.0mm thick operate at gentle speed with **side guided frame** and **cross support** to provide good support to the weight of the manure.

